Scand J Work Environ Health 1975;1(4):249-253

<https://doi.org/10.5271/sjweh.2841>

Issue date: Dec 1975

Effects of a welding helmet and dust respirators on respiration at rest and during exercise.

by [White T](#), [Schütz A](#), [Lundgren K-M](#)

Key terms: [carbon dioxide](#); [carbon dioxide tension](#); [dust respirator](#); [exercise](#); [experimental physiology](#); [respiration](#); [rest](#); [ventilation](#); [welding helmet](#)

This article in PubMed: www.ncbi.nlm.nih.gov/pubmed/1228904

This work is licensed under a [Creative Commons Attribution 4.0 International License](https://creativecommons.org/licenses/by/4.0/).

Effects of a welding helmet and dust respirators on respiration at rest and during exercise

by THOMAS WHITE, M.D.,¹ ANDREJS SCHÜTZ, B.Sc.,² and KARL-MAGNUS LUNDGREN, M.D.³

WHITE, T., SCHÜTZ, A. and LUNDGREN, K.-M. Effects of a welding helmet and dust respirators on respiration at rest and during exercise. *Scand. j. work environ. & health* 1 (1975) 249—254. The influence of welders' protective devices on respiration at rest and during exercise was studied under laboratory conditions. During exercise the devices caused increased ventilation and increased arterial carbon dioxide tension. In the case of the welding helmet the increase was probably a consequence of increased dead space. It is concluded that the physiological affects on respiration are of minor importance in themselves, but they should be taken into account when the degree of exposure to welding fumes is evaluated.

Key words: experimental physiology, welding helmet, dust respirator, respiration, ventilation, carbon dioxide tension, exercise.

Electric welding with coated electrodes can cause headache, nausea, and excessive fatigue. These symptoms may be caused by toxic substances in the fumes coming from the welding rods.

It is difficult to estimate the amount of fumes actually inhaled because the breathing pattern, the total pulmonary ventilation, and the access of the fumes to the face is likely to be influenced by factors such as the level of physical effort and the protective devices used. It has been found, however, that the concentration of welding fumes can be two to three times lower inside a welding helmet than outside it (Schütz, unpublished results). The difference in concentration may partly be due to the fact that the air inside the helmet also includes expired air, from

which part of the fumes has been removed by the lungs.

The objective of the present investigation was to determine whether the use of a welding helmet and a dust respirator affects respiration.

MATERIAL AND METHODS

Subjects

Six male shipyard welders, who were accustomed to the protective devices and who were experienced in electric welding, volunteered to take part in the study after the nature of the procedures was explained to them. They were informed that the experiments were aimed at improving the working conditions of welders in general but that they themselves would not necessarily benefit from the experiments. One subject (no. 1) had had pulmonary tuberculosis about 25 years earlier. All of the subjects were healthy at the time of the investigation, however, and a routine physical examination produced no abnormal findings.

¹ Department of Clinical Physiology, University of Lund, Lund, Sweden.

² Department of Occupational Medicine, University Hospital, Lund, Sweden.

³ Department of Medicine, Öresundsvarvet Shipyard, Landskrona, Sweden.

Reprint requests to: Mr. Andrejs Schütz, Yrkesmedicinska kliniken, Lasarettet, S-221 85 Lund, Sweden.

Equipment

Three types of protective devices were tested. All subjects used a skullguard/welding helmet combination (Tegma, Malmö, catalog no. 34950) (fig. 1). In addition two types of colloidal dust respirators were tested, either separately or in combination with the helmet. Subjects 1, 2, and 3 used a respirator with a prolonged exhalation valve directed downwards (Bicapa, Stockholm, catalog no. 2622). Subjects 4, 5, and 6 used a respirator consisting of a facepiece connected by means of a breathing tube to a belt-attached filter holder (Draeger, Lübeck, catalog no. RM 8740).

The welding helmet was attached to the skullguard with a mechanism which permitted the welder to swing the helmet up on the skullguard when not in use. When swung down in welding position, the helmet fitted close to the brim of the skullguard.

Methods

In a preliminary examination the results of conventional dynamic spirometry, a resting 12-lead electrocardiogram (ECG), and an exercise test on a bicycle ergometer with ECG recording were normal. During the exercise test the subjects were tested with an initial work load of 50 W and stepwise increments of 50 W until exhaustion. At each level the subjects were required to attain a steady state, as judged from the heart rate (increase in heart rate not more than four beats per minute between two measurements with an interval of 2 min), before moving to a higher level. The maximal physical work capacity was defined as the highest level at which the subject achieved a steady state.

An ECG was also recorded while the subject welded. During one ordinary work day a 12-h ECG recording was made on a portable lightweight tape recorder. Heart rate was measured from the ECG.

During the experiment an ECG with chest leads was recorded at 2-min intervals (at rest) or continuously (during exercise).

A teflon catheter was introduced percutaneously into the left brachial artery by the Seldinger technique. Arterial blood samples were obtained anaerobically and analyzed immediately. Arterial tensions

Fig. 1. Skullguard/welding helmet combination. The subject wore the device during the entire experimental procedure. (Photo A. Rosengren)

of oxygen (PaO_2) and of carbon dioxide (PaCO_2) were determined directly by conventional blood gas electrodes (Eschweiler, Keil, Germany), and pH was determined according to Astrup (Radiometer, Copenhagen, Denmark).

The tidal air of five of the six subjects was measured by a strain-gauge technique. A mercury-filled silastic tube was attached to the ventral circumference of the chest, and a constant voltage was applied to the

Table 1. Physiological measurements from six subjects at rest and during exercise. The subjects wore the skullguard with the welding helmet turned up (fig 1).

Sub- ject	Age (yr)		Heart rate (beats/min)	Respir- atory rate (breaths/ min)	Ventil- ation (l/min)	P _a CO ₂ (mm Hg)	P _a O ₂ (mm Hg)	pH
1	51	{Rest 75 W	84—87 131—148	— 24—28	— —	38.5—39.5 38.5—39.0	76—80 80—84	7.40—7.42 7.38
2	37	{Rest 35 W	73—79 130—144	20—23 28—31	7—8 13—16	39.5—41.0 38.5—42.5	70—77 75—81	7.42—7.43 7.38—7.42
3	37	{Rest 75 W	65—72 116—132	13—14 21—24	13—16 30	38.0—39.0 36.5—37.5	80—91 89—92	7.42—7.43 7.39—7.42
4	39	{Rest 100 W	48—54 100—120	9—13 17—20	9—10 57—69	39.0—40.5 37.0—41.5	99—100 92—95	7.38 7.35—7.41
5	38	{Rest 60 W	79—88 116—120	14—16 18—21	8—11 52—71	36.0—36.5 33.0—36.5	88—92 85—92	7.40—7.41 7.41—7.45
6	33	{Rest 70 W	81—87 120—129	13—15 19—22	5—8 33—48	38.0—38.5 35.5—40.0	85—87 83—89	7.41 7.38—7.42

mercury column. By means of a modified Wheatstone bridge arrangement, an electric signal proportional to the stretching of the tube was recorded on an ink-writer. The respiratory chest movements thus recorded were calibrated in terms of breathing volumes by letting the subject breathe into a spirometer with the silastic tube in position on the chest. The measurement was carried out immediately after the test period while the subject was still sitting on the bicycle ergometer.

Experimental design

Measurements were first made at rest while the subject sat comfortably in a reclining chair. Exercise was then performed on a bicycle ergometer (Siemens-Elcoma AB, Stockholm, Sweden). The work load (table 1) was about one-third or one-half of the subject's maximal physical work capacity and was similar to that measured during welding in the shipyard.

In order to obtain steady-state conditions, we allowed at least 6 min to pass before making measurements at rest, and at least 8 min passed before measurements were made during work. As the collection of blood samples, the ECG recording, and the ventilation measurement took a

Fig. 2. Subject no. 1; work load 75 W. The hatched bar represents the time when the helmet was in front of the face. Filled circles represent heart rate; and open circles, respiration rate.

certain period of time, usually less than 2 min, and they were begun after 6—8 min, the duration of each control or experimental period was 6—8 min (at rest) and 8—10 min (during exercise). Before and after each period of breathing with a protective device there was a control period. Thus the protocol for the continuous bicycle ergometer exercise, when only the helmet was being tested (subjects 2 and 3), was 8—10 min without a protective device, 8—10 minutes with the skullguard/helmet combination, and 8—10 min again without a protective device, the

complete test lasting approximately 30 min. When the welding helmet and dust respirator were tested separately and combined (subjects 4, 5, and 6), exercise lasted approximately 70 min. Perfect steady-state conditions, as judged from the heart rate, were not achieved, since the heart rate tended to be somewhat higher towards the end of the exercise period than after the initial 8 min of work (fig. 2).

The room temperature was approximately 20°C.

RESULTS

It can be seen in fig. 3 that, at rest, the combined use of a dust respirator and a welding helmet mounted on a skullguard caused an increased PaCO_2 in two of the subjects (no. 1 and 2), and an increased pulmonary ventilation in two (no. 2 and 3). The dust respirator alone increased the ventilation of subjects 4, 5, and 6.

More conspicuous effects were produced during exercise (fig. 4). With only two

exceptions the welding helmet and dust respirator increased both pulmonary ventilation and PaCO_2 .

When the subjects were questioned, they stated that breathing during exercise was "heavier" with than without the protective devices. The face also became warm behind the helmet. Otherwise there were no complaints.

DISCUSSION AND CONCLUSIONS

Increased external respiratory resistance during exercise is known to influence respiration (4, 6). It may also increase alveolar carbon dioxide tension (4, 6). The results of our experiment with dust respirators could be proof of this increase. However, the welding helmet used in our experiment produced similar effects despite free access to the ambient air and presumably negligible resistance. It should be noted that in the experiments there were no respiratory valves or mouthpieces and the protective devices were worn just as they would be worn during welding work in a shipyard.

The increase in ventilation and in arterial carbon dioxide tension that occurred when the helmet was worn is most readily explained by the possibility that the helmet acted to produce an increased "dead space." The effect appeared to be small or absent at rest, but obvious during exercise at a work load similar to that attained during actual welding work. It is unlikely that "psychogenic" hyperventilation occurred during the experiments since it would have produced a lowered PaCO_2 , and a lowered PaCO_2 rarely occurred. Another possible explanation

Fig. 3. Arterial carbon dioxide tension (PaCO_2) and pulmonary ventilation ($\dot{V}_E$) at rest; breathing with free face (helmet turned up) and breathing with the welding helmet or dust respirator. Control values with free face are means of periods immediately before and immediately after the period with the helmet or respirator. Subjects 1, 2, 3, 4, 5, and 6 are represented by symbols ∇ , Δ , $\square$, $\circ$, $\triangleleft$, and $\triangleright$, respectively. Open symbols denote the use of the helmet; filled symbols denote the use of the respirator; symbols containing the horizontal bar denote the simultaneous use of the helmet and respirator. The line of identity is shown.

Fig. 4. Arterial carbon dioxide tension (PaCO₂) and pulmonary ventilation (V_E) during exercise; breathing with free face (helmet turned up) and breathing with the welding helmet or dust respirator. Control values with free face are means of periods immediately before and immediately after the period with the helmet or respirator. Subjects 1, 2, 3, 4, 5, and 6 are represented by symbols ▽, △, □, ○, ◁, and ▷, respectively. Open symbols denote the use of the helmet; filled symbols denote the use of the respirator; symbols containing the horizontal bar denote the simultaneous use of the helmet and respirator. The line of identity is shown.

for the increased PaCO₂ could be that there was an increase in carbon dioxide production, which was not measured in the present experiments. However, we think it is reasonable to assume that the oxygen consumption and the carbon dioxide production did not change significantly because the external work on the bicycle ergometer was constant. Progressive ventilatory changes during the work period were excluded by the observations made during the control periods (fig. 2).

We do not believe that an increased ventilation and/or a moderate increase in

PaCO₂ represents a "health hazard" in the conventional sense, but either may contribute to fatigue or to other unpleasant experiences which occur during and immediately after work. In our opinion a less spacious helmet would produce less "dead space," and thus pulmonary ventilation and PaCO₂ would increase less.

During welding, toxic substances may be absorbed from inhaled fumes, which can, as indicated in several reports (2, 3, 5), also have local effects, e.g., bronchitis. The increased pulmonary ventilation produced by the welding shield probably means that an increased amount of the fumes is absorbed. Therefore the concentration of toxic substances in the breathing zone is an insufficient measure of the degree of exposure. Further investigations are needed to clarify the situation. However, it is quite evident that measurements made with the subject at rest do not always permit conclusions about events occurring during actual work (1).

REFERENCES

1. ÅSTRAND, I., EHRNER-SAMUEL, H., KILBOM, Å. and ÖVRUM, P. Toluene exposure: Concentration in alveolar air and blood at rest and during exposure. *Work-environ.-health* 9 (1972) 119-130.
2. AHLMARK, A. and LÖNNBERG, B. En hälsundersökning av 110 elektrosvetsare med långvarig arbetsanamnes [Health examination of 110 electric welders with a history of long-term exposure]. *Nord. hyg. tidskr.* 11-12 (1953) 238-249.
3. AXELSON, O. "Svetsarbronkit" — epidemiologi i företagshälsovården ["Welders' bronchitis" — Epidemiology in occupational health service]. *Läkartidningen* 71 (1974) 479-482.
4. DEMEDTS, M. and ANTHONISEN, N. R. Effects of increased external airway resistance during steady state exercise. *J. appl. physiol.* 35 (1973) 361-366.
5. FOGH, A., FROST, J. and GEORG, J. Respiratory symptoms and pulmonary function in welders. *Ann. occup. hyg.* 12 (1969) 213-218.
6. STRINDBERG, L., JOHANSSON, L., CARLSSON, A., LJUNGQVIST, E. and ÅSTRAND, I. Fysiologisk belastning vid ökat andningsmotstånd orsakat av andningskydd med filter [Physiological load and increased breathing resistance caused by filter respirators]. *Arbete och hälsa* (1974) 5. (Summary in English)

Received for publication: 1975-07-16